

View Online at <https://aerobasegroup.com/nsn/5340-01-316-1507>

Mounting Hole Type:

Counterbored and plain

First Leg Length:

1.780 inches

Second Leg Length:

3.120 inches

Second Leg Width:

1.250 inches

First Leg Hole Diameter:

0.344 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg End Radius:

0.690 inches

Second Leg End Radius:

0.690 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 81.0 degrees and 85.0 degrees

Second Leg Offset Angle:

Between 17.0 degrees and 21.0 degrees

Special Features:

Rh usage; opposite of p/n 12342135

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9 t4 federal specification single material response or astm b221 t4 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.