

View Online at <https://aerobasegroup.com/nsn/5340-01-316-1793>

Mounting Hole Type:

Plain

First Leg Length:

5.170 inches

Second Leg Length:

17.460 inches

Second Leg Width:

4.250 inches

Second Leg End Width:

3.000 inches

First Leg Hole Diameter:

0.286 mils and 0.296 centimeters

Second Leg Hole Diameter:

0.280 inches

Second Leg Distance Between Upper Hole Centers Along Width:

2.115 inches

Second Leg Distance Between Lower Hole Centers Along Width:

2.088 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.368 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.250 inches

First Leg End Width:

1.000 inches

First Leg Distance Between Upper Hole Centers Along Width:

2.000 inches

First Leg Distance Between Hole Centers Along Length:

1.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.605 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 of standard range single treatment response

Second Leg Chamfer Angle:

45.0 of standard range single treatment response

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response or qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-83286 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83286 spec.