

View Online at <https://aerobasegroup.com/nsn/5340-01-316-1793>

**Mounting Hole Type:**

Plain

**First Leg Length:**

5.170 inches

**Second Leg Length:**

17.460 inches

**Second Leg Width:**

4.250 inches

**Second Leg End Width:**

3.000 inches

**First Leg Hole Diameter:**

0.286 mils and 0.296 centimeters

**Second Leg Hole Diameter:**

0.280 inches

**Second Leg Distance Between Upper Hole Centers Along Width:**

2.115 inches

**Second Leg Distance Between Lower Hole Centers Along Width:**

2.088 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.368 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

4.250 inches

**First Leg End Width:**

1.000 inches

**First Leg Distance Between Upper Hole Centers Along Width:**

2.000 inches

**First Leg Distance Between Hole Centers Along Length:**

1.750 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.605 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Chamfered ends

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 of standard range single treatment response

**Second Leg Chamfer Angle:**

45.0 of standard range single treatment response

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-225/8, t6 federal specification single material response or qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-83286 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-83286 spec.