NSN 5340-01-317-4160

Helical Compression Spring Retainer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-01-317-4160 |
|--|
| Casehardening Indicator: |
| Not casehardened |
| Bolt Circle Diameter: |
| 1.500 inches |
| Flange Diameter: |
| Between 2.177 inches and 2.187 inches |
| Flange Thickness: |
| 0.312 inches |
| Overall Height: |
| 2.437 inches |
| Mounting Hole Diameter: |
| Between 0.404 inches and 0.414 inches |
| Body Outside Diameter: |
| Between 1.248 inches and 1.249 inches |
| Body Inside Diameter: |
| 0.500 inches |
| End Hole Diameter: |
| Between 0.150 inches and 0.760 inches |
| Material: |
| Steel, aisi 1015 or steel, aisi 1016 or steel, aisi 1017 or steel, aisi 1018 or steel, aisi 1019 or steel, aisi 1020 or steel, aisi 1021 or steel, |
| aisi 1022 or steel, aisi 1023 or steel, aisi 1024 or steel, aisi 1025 |
| Material: |
| Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or |
| steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 |
| Material Specification: |
| Aisi 1015 assn standard 1st material response and aisi 1016 assn standard 2nd material response and aisi 1017 assn standard 3rd material |
| response and aisi 1018 assn standard 4th material response and aisi 1019 assn standard 5th material response and aisi 1020 assn standard |
| 6th material response and aisi 1021 assn standard 7th material response and aisi 1022 assn standard 8th material response and aisi 1023 |
| assn standard 9th material response and aisi 1024 assn standard 10th material response and aisi 1025 assn standard 11th material |
| response |
| Surface Treatment: |
| Phosphate manganese |
| Surface Treatment Specification: |
| Dod-p-16232, ty m, cl 1 def stan/spec single treatment response |
| Style Designator: |
| Irregular |
| Surface Treatment: |
| Phosphate manganese, dod-p-16232, ty m, cl 1 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No Eiia

Demilitarization: