

View Online at <https://aerobasegroup.com/nsn/5340-01-317-4162>

**Counterbore Diameter:**

2.3300 inches

**Overall Height:**

1.3800 inches

**First Step Diameter:**

2.6200 inches

**First Step Length:**

0.7750 inches

**Second Step Diameter:**

Between 3.7410 inches and 3.7420 inches

**Bore Diameter:**

Between 1.3740 inches and 1.3760 inches

**Design Type:**

Solid

**Countersink Diameter:**

2.4000 inches

**End Diameter:**

2.4000 inches

**Distance From End To First Step:**

0.3800 inches

**Counterbore Length:**

0.4550 inches

**Special Features:**

3 holes in flange 0.209 in. Min, 0.218 in. Maximum dia, 2 open slots; 1 slot 0.250 in. W, 1 slot 0.500 in. W

**Material:**

Aluminum alloy, qq-a-225/8, alloy 6061, t6 or aluminum alloy, qq-a-200/8, alloy 6061, t6510

**Material:**

Aluminum alloy 6061 or aluminum alloy 6061

**Material Specification:**

Qq-a-225/8, alloy 6061, t6 federal specification 1st material response and qq-a-200/8, alloy 6061, t6510 federal specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, class 1 military specification single treatment response

**Surface Treatment:**

Anodized, mil-a-8625, type 2, class 1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T319-e

**Mil-std (military Standard):**

Mil-a-8625 spec.