Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-317-5243



Mounting Hole Type:
Mounting Hole Type: Plain
First Leg Length:
4.938 inches
Second Leg Length:
5.750 inches
Reinforcement Method (non-core):
Gusset first leg
End Application:
2350-01-305-0028; m109a3e2
Second Leg Width:
3.250 inches
First Leg Slot Length:
0.938 inches
First Leg Slot Width:
0.435 inches
Second Leg Distance Between Hole Centers Along Width:
1.500 inches
Second Leg Distance Between Hole Centers Along Length:
4.250 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.875 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.750 inches
Second Leg Slot Length:
0.938 inches
Second Leg Slot Width:
0.435 inches
First Leg Thickness:
0.375 inches
Second Leg Thickness:
0.438 inches
First Leg Width:
3.250 inches
First Leg Distance Between Hole Centers Along Length:
2.125 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
1.000 inches
First Leg Style:
Square

NSN 5340-01-317-5243

Angle Bracket - Page 2 of 2



Firs	st Leg Hole Arrangement Style:
2 sl	lots
Sec	cond Leg Style:
Squ	uare
Sec	cond Leg Hole Arrangement Style:
2 sl	lots
Sec	cond Leg Relationship To First Leg:
Not	t identical
Spe	ecial Features:
Firs	st leg has u-shaped groove 2.25 in.Long, 0.127 in.Deep located 2.75 in.From second leg edge.Second leg has notch 0.375 in.Wide
run	ning full length. Also has 0.236 in. Dia. Hole located 3.50 in. From edge along length and 0.875 in. From edge along width.
Sty	/le Designator:
Ang	gle
She	elf Life:
N/a	a
Uni	it Of Measure:
Dei	militarization:
No	
Fiig	g:
A04	42a0