## NSN 5340-01-318-2052

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-318-2052

Mounting Hole Type:
Plain
First Leg Length:
1.700 inches
Second Leg Length:
Between 4.700 inches and 5.000 inches
Second Leg Width:
1.500 inches
First Leg Slot Length:
0.500 inches
First Leg Slot Width:
Between 0.194 inches and 0.249 inches
Second Leg Hole Diameter:
Between 0.468 inches and 0.521 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.750 inches
Second Leg Distance From Edge To Hole Center Along Length:
Between 0.700 inches and 1.000 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
Center Section Height:
2.500 inches
Center Section Width:
1.500 inches
Center Section Thickness:
0.125 inches
First Leg Width:
1.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
0.700 inches
First Leg End Radius:
0.750 inches
Second Leg End Radius:
0.750 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:
One slot

One slot

## NSN 5340-01-318-2052

Double Angle Bracket - Page 2 of 2



Second Leg Style:
End radius
Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Aluminum alloy 5083 or aluminum alloy 5086
Material Specification:
Qq-a-250/6 h323 federal specification 1st material response or qq-a-250/7 h32 federal specification 2nd material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 cl 1a military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.