

View Online at <https://aerobasegroup.com/nsn/5340-01-318-2910>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 0.580 inches and 0.620 inches

**Second Leg Length:**

Between 0.720 inches and 0.760 inches

**End Application:**

2350-01-305-0028; m109a3e2

**Second Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Hole Diameter:**

Between 0.213 inches and 0.223 inches

**Second Leg Hole Diameter:**

Between 0.213 inches and 0.223 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**Center Section Height:**

Between 1.280 inches and 1.320 inches

**Center Section Width:**

Between 0.480 inches and 0.520 inches

**Center Section Thickness:**

0.040 inches

**First Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.238 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 302

**Material Specification:**

Mil-s-5059 military specification all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification all treatment responses

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-5059 spec.