NSN 5340-01-318-3404

Helical Compression Spring Seat - Page 1 of 1



| , | View Online at https://aerobasegroup.com/nsn/5340-01-318-3404 |
|---|---|
| (| Counterbore Diameter: |
| ı | Between 0.6250 inches and 0.6270 inches |
| (| Overall Height: |
| | 1.4370 inches |
| I | First Step Diameter: |
| ı | Between 0.9930 inches and 0.9950 inches |
| ı | Bore Diameter: |
| I | Between 0.4370 inches and 0.4371 inches |
| ı | Design Type: |
| , | Solid |
| I | End Diameter: |
| (| 0.6250 inches |
| I | Distance From End To First Step: |
| (| 0.3620 inches |
| ; | Special Features: |
| (| 0.2800 in. W and 0.6690 in. Deep and equally spaced four slots |
| ı | Material: |
| , | Steel, astm a108, grade 1020 |
| I | Material: |
| , | Steel comp 1020 |
| ı | Material Specification: |
| , | Astm a108, grade 1020 assn standard single material response |
| ; | Surface Treatment: |
| ı | Phosphate manganese |
| , | Surface Treatment Specification: |
| I | Dod-p-16232, ty m, cl 2 def stan/spec single treatment response |
| ; | Surface Treatment: |
| ı | Phosphate, dod-p-16232, ty m, cl 2 |
| , | Shelf Life: |
| I | N/a |
| (| Unit Of Measure: |
| | - |
| I | Demilitarization: |
| ı | No |

Fiig: T319-e