NSN 5340-01-318-6866

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-318-6866

Mounting Hole Type:PlainFirst Leg Length:1.000 inchesSecond Leg Length:2.000 inchesSecond Leg Width:2.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.380 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.380 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.125 inches6.125 inches0.125 inchesFirst Leg Thickness:0.125 inchesFirst Leg Width:
First Leg Length: 1.000 inches Second Leg Length: 2.000 inches Second Leg Width: 2.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches 0.125 inches
1.000 inches Second Leg Length: 2.000 inches Second Leg Width: 2.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches O.125 inches
Second Leg Length: 2.000 inches Second Leg Width: 2.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
2.000 inches Second Leg Width: 2.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
Second Leg Width: 2.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
2.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
Second Leg Distance From Edge To Hole Center Along Width: 0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
0.380 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
0.500 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches
0.125 inches Second Leg Thickness: 0.125 inches
Second Leg Thickness: 0.125 inches
0.125 inches
First Leg Width:
2.250 inches
Second Leg Style:
Square
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0

NSN 5340-01-318-6866

Angle Bracket - Page 2 of 2

Mil-std (military Standard):

Mil-c-5541 spec.

