

View Online at <https://aerobasegroup.com/nsn/5340-01-318-8272>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.750 inches

**Second Leg Length:**

8.500 inches

**Reinforcement Method:**

Turned edge both legs and gusset both legs

**Second Leg Width:**

11.500 inches

**First Leg Hole Diameter:**

Between 0.610 inches and 0.640 inches

**Second Leg Hole Diameter:**

Between 0.516 inches and 0.546 inches

**Second Leg Distance Between Hole Centers Along Width:**

8.500 inches

**Second Leg Distance Between Hole Centers Along Length:**

3.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

11.500 inches

**First Leg Distance Between Hole Centers Along Width:**

8.625 inches

**First Leg Distance Between Hole Centers Along Length:**

0.450 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.438 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.180 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Color green 383

**Material:**

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel

**Material Specification:**

Astm a635 assn standard 1st material response or astm a635 assn standard 1st material response or astm a635 assn standard 1st material response or astm a635, comp 1017 assn standard 1st material response or astm a635, comp 1018 assn standard 1st material response or astm a635, comp 1019 assn standard 1st material response or astm a635 comp 1020 assn standard 1st material response or astm a283, grade c, hr or p and o assn standard 1st material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.