

View Online at <https://aerobasegroup.com/nsn/5340-01-318-8272>

Mounting Hole Type:

Plain

First Leg Length:

2.750 inches

Second Leg Length:

8.500 inches

Reinforcement Method:

Turned edge both legs and gusset both legs

Second Leg Width:

11.500 inches

First Leg Hole Diameter:

Between 0.610 inches and 0.640 inches

Second Leg Hole Diameter:

Between 0.516 inches and 0.546 inches

Second Leg Distance Between Hole Centers Along Width:

8.500 inches

Second Leg Distance Between Hole Centers Along Length:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

11.500 inches

First Leg Distance Between Hole Centers Along Width:

8.625 inches

First Leg Distance Between Hole Centers Along Length:

0.450 inches

First Leg Distance From Edge To Hole Center Along Width:

1.438 inches

First Leg Distance From Edge To Hole Center Along Length:

1.180 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Color green 383

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel

Material Specification:

Astm a635 assn standard 1st material response or astm a635 assn standard 1st material response or astm a635 assn standard 1st material response or astm a635, comp 1017 assn standard 1st material response or astm a635, comp 1018 assn standard 1st material response or astm a635, comp 1019 assn standard 1st material response or astm a635 comp 1020 assn standard 1st material response or astm a283, grade c, hr or p and o assn standard 1st material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.