

View Online at <https://aerobasegroup.com/nsn/5340-01-319-4865>

**Mounting Hole Type:**

Plain

**First Leg Length:**

7.620 inches

**Second Leg Length:**

14.000 inches

**Reinforcement Method (non-core):**

Gusset first leg

**Second Leg Width:**

15.250 inches

**First Leg Hole Diameter:**

Between 0.436 inches and 0.443 inches

**Second Leg Hole Diameter:**

Between 0.436 inches and 0.443 inches

**Second Leg Distance Between Hole Centers Along Width:**

6.090 inches

**Second Leg Distance Between Hole Centers Along Length:**

3.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

4.580 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.620 inches

**First Leg Thickness:**

0.120 inches

**Second Leg Thickness:**

0.120 inches

**Center Section Height:**

11.440 inches

**Center Section Width:**

15.250 inches

**Center Section Thickness:**

0.120 inches

**First Leg Width:**

15.250 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

4.500 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

4.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

3.125 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1009

**Material Specification:**

Astm a366 assn standard single material response or astm a569 assn standard single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-t-704, ty f military specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-t-704 spec.