## NSN 5340-01-319-4865

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-319-4865

Mounting Hele Type
Mounting Hole Type: Plain
First Leg Length: 7.620 inches
Second Leg Length:
14.000 inches
Reinforcement Method (non-core):
Gusset first leg
Second Leg Width:
15.250 inches
First Leg Hole Diameter:
Between 0.436 inches and 0.443 inches
Second Leg Hole Diameter:
Between 0.436 inches and 0.443 inches
Second Leg Distance Between Hole Centers Along Width:
6.090 inches
Second Leg Distance Between Hole Centers Along Length:
3.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
4.580 inches
Second Leg Distance From Edge To Hole Center Along Length:
1.620 inches
First Leg Thickness:
0.120 inches
Second Leg Thickness:
0.120 inches
Center Section Height:
11.440 inches
Center Section Width:
15.250 inches
Center Section Thickness:
0.120 inches
First Leg Width:
15.250 inches
First Leg Distance Between First And Second Hole Centers Along Width:
4.500 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
4.500 inches
First Leg Distance From Edge To Hole Center Along Width:
3.125 inches
First Leg Distance From Edge To Hole Center Along Length: 0.750 inches
U.750 IIIGHeS

## NSN 5340-01-319-4865

Double Angle Bracket - Page 2 of 2



First Leg Style:	
Square	
First Leg Hole Arrangement Style:	
Three holes	
Second Leg Style:	
Square	
Second Leg Hole Arrangement Style:	
Four holes	
Second Leg Relationship To First Leg:	
Not identical	
First Leg Angle:	
90.0 degrees	
Second Leg Angle:	
90.0 degrees	
Material:	
Steel comp 1009	
Material Specification:	
Astm a366 assn standard single material response or astm a569 assn standard single material response	
Surface Treatment:	
Paint	
Surface Treatment Specification:	
Mil-t-704, ty f military specification single treatment response	
Style Designator:	
Double angle	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A042a0	
Mil-std (military Standard):	
Mil-t-704 spec.	