NSN 5340-01-319-4866

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-319-4866

Mounting Hole Type:
Plain
First Leg Length:
1.880 inches
Second Leg Length:
19.740 inches
Second Leg Width:
15.250 inches
First Leg Slot Length:
Between 0.750 inches and 0.812 inches
First Leg Slot Width:
Between 0.436 inches and 0.443 inches
Second Leg Distance Between Hole Centers Along Width:
6.090 inches
Second Leg Distance Between Hole Centers Along Length:
3.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
4.580 inches
Second Leg Distance From Edge To Hole Center Along Length:
1.495 inches
Second Leg Slot Length:
Between 0.750 inches and 0.812 inches
Second Leg Slot Width:
Between 0.436 inches and 0.443 inches
First Leg Thickness:
0.120 inches
Second Leg Thickness:
0.120 inches
Center Section Height:
11.440 inches
Center Section Width:
15.250 inches
Center Section Thickness:
0.120 inches
First Leg Width:
15.250 inches
First Leg Distance Between First And Second Hole Centers Along Width:
4.500 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
4.500 inches
First Leg Distance From Edge To Hole Center Along Width:
2.105 inches

3.125 inches

NSN 5340-01-319-4866

Double Angle Bracket - Page 2 of 2



First Leg Distance From Edge To Hole Center Along Length:
0.755 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
3 slots
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
4 slots
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Special Features:
Bend radius 0.250 in.
Material:
Steel
Material Specification:
Astm a366 assn standard single material response or astm a569 assn standard single material response
Surface Treatment:
Paint
Surface Treatment Specification:
Mil-t-704, ty f military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-t-704 spec.