

View Online at <https://aerobasegroup.com/nsn/5340-01-319-4866>

Mounting Hole Type:

Plain

First Leg Length:

1.880 inches

Second Leg Length:

19.740 inches

Second Leg Width:

15.250 inches

First Leg Slot Length:

Between 0.750 inches and 0.812 inches

First Leg Slot Width:

Between 0.436 inches and 0.443 inches

Second Leg Distance Between Hole Centers Along Width:

6.090 inches

Second Leg Distance Between Hole Centers Along Length:

3.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

4.580 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.495 inches

Second Leg Slot Length:

Between 0.750 inches and 0.812 inches

Second Leg Slot Width:

Between 0.436 inches and 0.443 inches

First Leg Thickness:

0.120 inches

Second Leg Thickness:

0.120 inches

Center Section Height:

11.440 inches

Center Section Width:

15.250 inches

Center Section Thickness:

0.120 inches

First Leg Width:

15.250 inches

First Leg Distance Between First And Second Hole Centers Along Width:

4.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

4.500 inches

First Leg Distance From Edge To Hole Center Along Width:

3.125 inches

First Leg Distance From Edge To Hole Center Along Length:

0.755 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

3 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

4 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Bend radius 0.250 in.

Material:

Steel

Material Specification:

Astm a366 assn standard single material response or astm a569 assn standard single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-t-704, ty f military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-t-704 spec.