

View Online at <https://aerobasegroup.com/nsn/5340-01-320-0949>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.620 inches

**Second Leg Length:**

2.620 inches

**Second Leg Width:**

2.940 inches

**Second Leg Corner Radius:**

1.000 inches

**First Leg Hole Diameter:**

Between 1.000 inches and 1.003 inches

**Second Leg Hole Diameter:**

Between 0.670 inches and 0.680 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.687 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.627 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.120 inches

**First Leg Thickness:**

0.750 inches

**First Leg Width:**

2.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.995 inches

**First Leg End Radius:**

1.000 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second corner radius on second leg 0.620 in.; first leg, two inline holes 0.250 in. Min 0.256 in. Maximum diameter spaced 1.625 in. From flat end; harden and temper to rockwell c35 to c40

**Material:**

Steel comp 416 or stainless steel

**Material Specification:**

Astm a582 assn standard 1st material response or astm a743, gr ca-15 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0