

View Online at <https://aerobasegroup.com/nsn/5340-01-320-0949>

Mounting Hole Type:

Plain

First Leg Length:

2.620 inches

Second Leg Length:

2.620 inches

Second Leg Width:

2.940 inches

Second Leg Corner Radius:

1.000 inches

First Leg Hole Diameter:

Between 1.000 inches and 1.003 inches

Second Leg Hole Diameter:

Between 0.670 inches and 0.680 inches

Second Leg Distance Between Hole Centers Along Width:

1.687 inches

Second Leg Distance Between Hole Centers Along Length:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.627 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.120 inches

First Leg Thickness:

0.750 inches

First Leg Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.995 inches

First Leg End Radius:

1.000 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second corner radius on second leg 0.620 in.; first leg, two inline holes 0.250 in. Min 0.256 in. Maximum diameter spaced 1.625 in. From flat end; harden and temper to rockwell c35 to c40

Material:

Steel comp 416 or stainless steel

Material Specification:

Astm a582 assn standard 1st material response or astm a743, gr ca-15 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0