NSN 5340-01-320-1081 Angle Bracket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-01-320-1081 |
|--|
| Mounting Hole Type: |
| Plain |
| First Leg Length: |
| 0.215 inches |
| Second Leg Length: |
| 0.300 inches |
| Second Leg Width: |
| 0.800 inches |
| Second Leg End Width: |
| 0.550 inches |
| Second Leg Hole Diameter: |
| Between 0.092 inches and 0.097 inches |
| Second Leg Distance Between Hole Centers Along Width: |
| 0.562 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.119 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.180 inches |
| First Leg Thickness: |
| 0.040 inches |
| Second Leg Thickness: |
| 0.040 inches |
| First Leg Width: |
| 8.000 inches |
| First Leg Hole Arrangement Style: |
| No hole |
| Second Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Chamfer Angle: |
| 45.0 degrees |
| Special Features: |
| Cut out in second leg 0.450 in. W, 0.220 in. Lg |
| Material: |
| Aluminum alloy 5052 or aluminum alloy 6063 |
| Material Specification: |
| Qq-a-250/8, h32 federal specification 1st material response or qq-a-200/9, t52 federal specification 2nd material response |
| Surface Treatment: |
| Chromate |

NSN 5340-01-320-1081

Angle Bracket - Page 2 of 2



| Surface Treatment Specification: |
|---|
| Mil-c-5541, cl 1a military specification single treatment response $$ |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/o |

Demilitarization:

Unit Of Measure:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.