NSN 5340-01-320-3583

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-320-3583
Mounting Hole Type:
Plain
First Leg Length:
Between 1.094 inches and 1.156 inches
Second Leg Length:
1.6826 inches
Second Leg Width:
Between 6.969 inches and 7.031 inches
First Leg Hole Diameter:
0.406 inches
Second Leg Hole Diameter:
0.390 inches
Second Leg Distance Between Hole Centers Along Width:
6.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
Between 0.469 inches and 0.531 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.438 inches
First Leg Thickness:
0.1196 inches
Second Leg Thickness:
0.1196 inches
Center Section Height:
0.5576 inches
Center Section Width:
Between 6.969 inches and 7.031 inches
Center Section Thickness:
0.1196 inches
First Leg Width:
Between 6.969 inches and 7.031 inches
First Leg Distance Between Hole Centers Along Width:
6.000 inches
First Leg Distance From Edge To Hole Center Along Width:
Between 0.469 inches and 0.531 inches
First Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:

Square

NSN 5340-01-320-3583

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Steel comp 4140
Material Specification:
Mil-s-18729, cond a military specification single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Dod-p-16232, ty m, cl 4 military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
- -
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-s-18729 spec.