

View Online at <https://aerobasegroup.com/nsn/5340-01-320-3583>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.094 inches and 1.156 inches

Second Leg Length:

1.6826 inches

Second Leg Width:

Between 6.969 inches and 7.031 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

0.390 inches

Second Leg Distance Between Hole Centers Along Width:

6.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.469 inches and 0.531 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.438 inches

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

Center Section Height:

0.5576 inches

Center Section Width:

Between 6.969 inches and 7.031 inches

Center Section Thickness:

0.1196 inches

First Leg Width:

Between 6.969 inches and 7.031 inches

First Leg Distance Between Hole Centers Along Width:

6.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.469 inches and 0.531 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 4140

Material Specification:

Mil-s-18729, cond a military specification single material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Dod-p-16232, ty m, cl 4 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.