

View Online at <https://aerobasegroup.com/nsn/5340-01-321-6169>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.261 inches and 0.266 inches

Edge Shape:

Rectangle, multi holes

Length:

25.210 inches

Body Thickness:

Between 0.250 inches and 0.260 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

End Application:

Amraam lau128 (aft)

Features Provided:

Special marking

Special Features:

Item has 6 holes diameter 0.261 to 0.266 thru, csk 0.510 in. X 100 deg, there are also 10 holes diameter 0.040 in. Requiring solid rivets, p/n ms20426ad3, that are installed iaw mil-std-403 w/exception that head of rivet to flush to 0.010 in. Below surface of cover, there are 12 holes diameter 0.266 to 0.271 in. Through 2 walls, these holes are 11 spaces @ 1.750 in. Equaling 19.250 in.; item also requires 2 channel gang nuts p/n 7002549-5

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11 type 2 t73510 or t73511 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 cl1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A531c0

Mil-std (military Standard):

Mil-std-403 spec.