NSN 5340-01-321-6169

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-321-6169

| Cross Sectional Shape: |
|--|
| Flat |
| Hole Diameter: |
| Between 0.261 inches and 0.266 inches |
| Edge Shape: |
| Rectangle, multi holes |
| Length: |
| 25.210 inches |
| Body Thickness: |
| Between 0.250 inches and 0.260 inches |
| Securing Device Type: |
| Special |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| End Application: |
| Amraam lau128 (aft) |
| Features Provided: |
| Special marking |
| Special Features: |
| Item has 6 holes diameter 0.261 to 0.266 thru, csk 0.510 in. X 100 deg, there are also 10 holes diameter 0.040 in. Requiring solid rivets, p/n |
| ms20426ad3, that are installed iaw mil-std-403 w/exception that head of rivet to flush to 0.010 in. Below syrface of cover, there are 12 holes |
| diameter 0.266 to 0.271 in. Through 2 walls, these holes are 11 spaces @ 1.750 in. Equaling 19.250 in.; item also requires 2 channel gang |
| nuts p/n 7002549-5 |
| Material: |
| Aluminum alloy 7075 |
| Material Specification: |
| Qq-a-200/11 type 2 t73510 or t73511 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 type 2 cl1 military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A531c0 |
| Mil-std (military Standard): |
| Mil-std-403 spec. |