

View Online at <https://aerobasegroup.com/nsn/5340-01-323-2356>

Mounting Hole Type:

Plain

First Leg Length:

2.750 inches

Second Leg Length:

8.500 inches

Reinforcement Method (non-core):

Turned edge both legs and gusset both legs

Second Leg Width:

11.500 inches

First Leg Hole Diameter:

Between 0.610 inches and 0.640 inches

Second Leg Hole Diameter:

Between 0.516 inches and 0.546 inches

Second Leg Distance Between Hole Centers Along Width:

8.500 inches

Second Leg Distance Between Hole Centers Along Length:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

11.500 inches

First Leg Distance Between Hole Centers Along Width:

7.620 inches

First Leg Distance Between Hole Centers Along Length:

0.450 inches

First Leg Distance From Edge To Hole Center Along Width:

1.940 inches

First Leg Distance From Edge To Hole Center Along Length:

1.180 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Color green 383

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.