

View Online at <https://aerobasegroup.com/nsn/5340-01-323-2356>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.750 inches

**Second Leg Length:**

8.500 inches

**Reinforcement Method (non-core):**

Turned edge both legs and gusset both legs

**Second Leg Width:**

11.500 inches

**First Leg Hole Diameter:**

Between 0.610 inches and 0.640 inches

**Second Leg Hole Diameter:**

Between 0.516 inches and 0.546 inches

**Second Leg Distance Between Hole Centers Along Width:**

8.500 inches

**Second Leg Distance Between Hole Centers Along Length:**

3.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

11.500 inches

**First Leg Distance Between Hole Centers Along Width:**

7.620 inches

**First Leg Distance Between Hole Centers Along Length:**

0.450 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.940 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.180 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Color green 383

**Material:**

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.