

View Online at <https://aerobasegroup.com/nsn/5340-01-323-8478>

Mounting Hole Type:

Plain

First Leg Length:

0.880 inches

Second Leg Length:

3.040 inches

Reinforcement Method (non-core):

Gusset both legs

Second Leg Width:

3.880 inches

Second Leg End Width:

3.120 inches

First Leg Hole Diameter:

Between 0.279 inches and 0.288 inches

Second Leg Hole Diameter:

Between 0.467 inches and 0.477 inches

Second Leg Distance Between Lower Hole Centers Along Width:

2.675 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.330 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.600 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.640 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

3.880 inches

First Leg Distance Between Hole Centers Along Width:

2.675 inches

First Leg Distance From Edge To Hole Center Along Width:

0.602 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.500 inches

First Leg Cutout Width:

2.080 inches

Second Leg Chamfer Angle:

45.0 degrees

Material:

Steel comp 321 or steel comp 347

Material Specification:

Ams 5510 assn standard 1st material response or ams 5512 assn standard 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0