NSN 5340-01-323-8478

Angle Bracket - Page 1 of 2

Mounting Hole Type:

Two holes



View Online at https://aerobasegroup.com/nsn/5340-01-323-8478

Plain
First Leg Length:
0.880 inches
Second Leg Length:
3.040 inches
Reinforcement Method (non-core):
Gusset both legs
Second Leg Width:
3.880 inches
Second Leg End Width:
3.120 inches
First Leg Hole Diameter:
Between 0.279 inches and 0.288 inches
Second Leg Hole Diameter:
Between 0.467 inches and 0.477 inches
Second Leg Distance Between Lower Hole Centers Along Width:
2.675 inches
Second Leg Distance Between Hole Centers Along Length:
1.000 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
1.330 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.600 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.640 inches
First Leg Thickness:
Between 0.057 inches and 0.069 inches
Second Leg Thickness:
Between 0.057 inches and 0.069 inches
First Leg Width:
3.880 inches
First Leg Distance Between Hole Centers Along Width:
2.675 inches
First Leg Distance From Edge To Hole Center Along Width:
0.602 inches
First Leg Distance From Edge To Hole Center Along Length:
0.300 inches
First Leg Style:
Cut out
First Leg Hole Arrangement Style:

NSN 5340-01-323-8478 Angle Bracket - Page 2 of 2



Second Leg Style:	
Chamfered ends	
Second Leg Hole Arrangement Style:	
Three holes	
Second Leg Relationship To First Leg:	
Not identical	
First Leg Angle:	
90.0 degrees	
First Leg Cutout Length:	
0.500 inches	
First Leg Cutout Width:	
2.080 inches	
Second Leg Chamfer Angle:	
45.0 degrees	
Material:	
Steel comp 321 or steel comp 347	
Material Specification:	
Ams 5510 assn standard 1st material response or ams 5512 assn standard 2nd material response	
Style Designator:	
Angle	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A042a0	