

View Online at <https://aerobasegroup.com/nsn/5340-01-323-9023>

Mounting Hole Type:

Plain

First Leg Length:

1.878 inches

Second Leg Length:

2.600 inches

Reinforcement Method (non-core):

Turned edge second leg and gusset second leg

Second Leg Width:

3.300 inches

First Leg Hole Diameter:

Between 0.279 inches and 0.288 inches

Second Leg Hole Diameter:

1.440 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.450 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.340 inches

First Leg Thickness:

Between 0.087 inches and 0.103 inches

Second Leg Thickness:

Between 0.087 inches and 0.103 inches

Center Section Height:

0.595 inches

Center Section Width:

3.060 inches

Center Section Thickness:

Between 0.087 inches and 0.103 inches

First Leg Width:

3.260 inches

First Leg Distance Between Hole Centers Along Width:

1.672 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

0.070 in. Hole diameter second leg along w one place; 0.180 in. Min and 0.186 in. Maximum hole diameter four places in 1.767 in. Bolt circle diameter all in second leg

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0