

View Online at <https://aerobasegroup.com/nsn/5340-01-324-0592>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.870 inches and 0.930 inches

Second Leg Length:

Between 1.090 inches and 1.150 inches

Second Leg Width:

Between 0.970 inches and 1.030 inches

Second Leg Corner Radius:

Between 0.280 inches and 0.340 inches

Second Leg End Width:

2.030 inches

First Leg Hole Diameter:

Between 0.227 inches and 0.233 inches

Second Leg Hole Diameter:

Between 0.128 inches and 0.134 inches

Second Leg Distance Between Lower Hole Centers Along Width:

Between 1.390 inches and 1.430 inches

Second Leg Distance Between Hole Centers Along Length:

0.230 mils and 0.290 centimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 0.670 inches and 0.730 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Thickness:

0.025 inches

Second Leg Thickness:

0.025 inches

First Leg Width:

Between 0.970 inches and 1.030 inches

First Leg Corner Radius:

Between 0.280 inches and 0.340 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.380 inches and 0.440 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Radius foot

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1095

Material Specification:

Mil-s-7947 cond a military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-7947 spec.