

View Online at <https://aerobasegroup.com/nsn/5340-01-325-2035>

Mounting Hole Type:

Plain

First Leg Length:

0.980 inches

Second Leg Length:

0.980 inches

End Application:

P/n4073475; f100pw0229 engine

Second Leg Width:

4.800 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

Between 0.248 inches and 0.253 inches

Second Leg Hole Diameter:

0.221 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.605 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

1.605 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.790 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.285 inches

First Leg Thickness:

Between 0.077 inches and 0.102 inches

Second Leg Thickness:

Between 0.077 inches and 0.102 inches

First Leg Width:

4.800 inches

First Leg Distance Between Hole Centers Along Width:

4.280 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.070 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.070 inches

First Leg Distance From Edge To Hole Center Along Width:

0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

0.616 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.280 inches

First Leg Cutout Width:

1.848 inches

Material:

Titanium alloy

Material Specification:

Ams4911 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0