

View Online at <https://aerobasegroup.com/nsn/5340-01-325-2060>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.208 inches and 0.213 inches

Width:

6.500 inches

Length:

10.250 inches

Hole Quantity Along Length:

3

Hole Quantity Along Width:

2

Distance Between Holes Along Length:

3.250 inches

Distance Between Holes Along Width:

4.597 inches

Distance From First Hole Centerline To End Along Length:

1.730 inches

Distance From First Hole Centerline To End Along Width:

1.880 inches

Body Thickness:

0.090 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Features Provided:

Sealing capability

Special Features:

Holes counterbored to 0.312 in. Dia, 0.035 in. Deep ten places; additional through holes 0.166 in. Min and 0.169 in. Maximum diameter four places; item includes four washers, p/n ms35338-78, four screws, p/n ms51957-15, 4 nuts, p/n m45938/1-5c, four washers, p/n ms15795-803, one gasket, p/n 420-5101317, one label plate, p/n 420-5101318 and one access cover plate, p/n 420-5101316

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-15090c, type 3 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-e-15090c spec.