NSN 5340-01-326-2268

Access Cover - Page 1 of 2

A531c0



View Online at https://aerobasegroup.com/nsn/5340-01-326-2268

| view Offiline at https://aerobasegroup.com/hish/o5+0-01-520-2200 |
|---|
| Cross Sectional Shape: |
| Flat |
| Hole Diameter: |
| 0.250 inches and 0.260 inches |
| Width: |
| 14.500 inches |
| Edge Shape: |
| Rectangle, four holes |
| Length: |
| 16.500 inches |
| Distance Between Holes Along Length: |
| 14.000 inches |
| Distance Between Holes Along Width: |
| 13.375 inches |
| Distance From First Hole Centerline To End Along Length: |
| 1.250 inches |
| Distance From First Hole Centerline To End Along Width: |
| 0.562 inches |
| Body Thickness: |
| 1.500 inches |
| Securing Device Type: |
| Special |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| Special Features: |
| 2.000 in. Min and 2.060 in. Maximum hole diameter one place, 0-ring boss port ms33649-12, tube size 0.750 in. Dia; rubber gaskets |
| twoeach |
| Material: |
| Steel |
| Material Specification: |
| Astm a36 assn standard single material response |
| Surface Treatment: |
| Paint |
| Surface Treatment Specification: |
| Mil-t-704, ty b military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

NSN 5340-01-326-2268

Access Cover - Page 2 of 2



Mil-std (military Standard):

Mil-t-704 spec.