

View Online at <https://aerobasegroup.com/nsn/5340-01-326-5029>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

2.000 inches

Second Leg Width:

15.000 inches

First Leg Hole Diameter:

0.440 inches

Second Leg Hole Diameter:

0.310 inches

Second Leg Distance Between Hole Centers Along Width:

3.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

7.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.120 inches

Second Leg Thickness:

0.120 inches

First Leg Width:

15.000 inches

First Leg Distance Between Hole Centers Along Width:

13.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

3.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

5.810 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg one corner chamfered

Material:

Steel comp 1010 or steel comp 1020

Material Specification:

Astm-a366 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-83286 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83286 spec.