

View Online at <https://aerobasegroup.com/nsn/5340-01-326-5029>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.000 inches

**Second Leg Length:**

2.000 inches

**Second Leg Width:**

15.000 inches

**First Leg Hole Diameter:**

0.440 inches

**Second Leg Hole Diameter:**

0.310 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

7.310 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Thickness:**

0.120 inches

**Second Leg Thickness:**

0.120 inches

**First Leg Width:**

15.000 inches

**First Leg Distance Between Hole Centers Along Width:**

13.000 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

3.500 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

5.810 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg one corner chamfered

**Material:**

Steel comp 1010 or steel comp 1020

**Material Specification:**

Astm-a366 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-83286 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-83286 spec.