NSN 5340-01-327-3578



Double Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-327-3578 **Mounting Hole Type:** Plain First Leg Length: 1.658 inches Second Leg Length: 3.500 inches Second Leg Width: 14.000 inches Second Leg Hole Diameter: Between 0.334 inches and 0.354 inches Second Leg Distance Between Hole Centers Along Width: 10.000 inches Second Leg Distance From Edge To Hole Center Along Width: 2.000 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.880 inches First Leg Thickness: Between 0.240 inches and 0.260 inches Second Leg Thickness: Between 0.240 inches and 0.260 inches **Center Section Height:** 1.062 inches **Center Section Width:** 14.000 inches **Center Section Thickness:** Between 0.240 inches and 0.260 inches First Leg Width: 14.000 inches First Leg Style: Square First Leg Hole Arrangement Style: No hole Second Leg Style: Square Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical First Leg Angle: 90.0 degrees

Second Leg Angle: 94.0 degrees

NSN 5340-01-327-3578

Double Angle Bracket - Page 2 of 2



| Material: |
|--|
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-200/8 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| $\label{eq:mil-a-8625} \mbox{Mil-a-8625, type 1 or type 2, cl 1 or cl 2 military specification single treatment response}$ |
| Style Designator: |
| Adjacent angles |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |