NSN 5340-01-327-7233

General Purpose Resilient Mount - Page 1 of 1



Inside Diameter:
Between 0.747 inches and 0.753 inches
Flange Thickness:
0.312 inches
Distance Between Mounting Hole Centers:
Between 4.745 inches and 4.755 inches
Flange Length:
Between 5.844 inches and 5.937 inches
Flange Width:
Between 6.344 inches and 6.437 inches
Distance From Flange To End:
Between 0.502 inches and 0.507 inches
Flange Mounting Hole Diameter:
Between 0.516 inches and 0.531 inches
Height:
Height: Between 2.788 inches and 2.828 inches
_
Between 2.788 inches and 2.828 inches
Between 2.788 inches and 2.828 inches Style Designator:
Between 2.788 inches and 2.828 inches Style Designator: Round w/flanged bushing two-hole flange
Between 2.788 inches and 2.828 inches Style Designator: Round w/flanged bushing two-hole flange Shelf Life:
Between 2.788 inches and 2.828 inches Style Designator: Round w/flanged bushing two-hole flange Shelf Life: N/a
Between 2.788 inches and 2.828 inches Style Designator: Round w/flanged bushing two-hole flange Shelf Life: N/a
Between 2.788 inches and 2.828 inches Style Designator: Round w/flanged bushing two-hole flange Shelf Life: N/a Unit Of Measure:

A535s0