

View Online at <https://aerobasegroup.com/nsn/5340-01-327-9976>

**Cross Sectional Shape:**

Flat

**Width:**

Between 6.880 inches and 6.902 inches

**Edge Shape:**

Rectangle, multi holes

**Length:**

Between 15.360 inches and 15.410 inches

**Hole Quantity Along Length:**

4

**Hole Quantity Along Width:**

2

**Body Thickness:**

0.063 inches

**Securing Device Type:**

Threaded fastener and turnlock fastener

**Mounting Opening Shape Style:**

Unthreaded hole

**End Application:**

An/alq-172

**Features Provided:**

Special marking

**Special Features:**

Item has 4 holes marked 'b' diameter 0.191 to 0.201 in. Along length at bottom of item w/c to c distances of 4.200 in. Porm 0.005 in., 2 holes marked 'a' diameter 0.140 to 0.149 in. And 80 holes marked 'c' diameter 0.151 to 0.161 in.; 'c' hole spacing along length is 7 spaces @ 0.250 in. Equaling 1.750 in. Total noncumulative and has 11 spaces @ 0.250 in. Equaling 2.750 inn. Tol noncumulative as well as 3 spaces @ 0.250 in. Equaling 0.750 in. Tol noncumulative along the width; item requires 4 fstnr turnlock studs p/n 2137240g00 (vendor item), 4 fstnr turnlock eyelets p/n 2135202g002(vendor item), 2 captive scr p/n 2487939g002, 2 retaining washers p/n 2627210g001(vendor item)and 4 pressure pads 2 has p/n 2628598g002, 1 w/p/n 2628625g001 and 1 with p/n 26286333g002(all pressure pads are vendor items)

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate and primer zinc chromate and enamel lusterless

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification 1st treatment response and tt-e-527 comp g federal specification 2nd treatment response and tt-p-1757 type 1 color y federal specification 3rd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**