NSN 5340-01-330-0566

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-330-0566

Cross Sectional Shape:
Flat, round rib reinforced
Hole Diameter:
Between 1.939 inches and 1.940 inches
Bolt Circle Diameter:
2.750 inches
Flange Thickness:
0.187 inches
Outside Diameter:
3.250 inches
Edge Shape:
Round, multi holes
Bolt Circle Hole Quantity:
4
Body Thickness:
0.375 inches
Securing Device Type:
Special
Mounting Opening Shape Style:
Unthreaded hole
Factories Described
Features Provided:
Observation facility
Observation facility
Observation facility Special Features:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, type 1 federal specification single treatment response
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, type 1 federal specification single treatment response Shelf Life:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, type 1 federal specification single treatment response Shelf Life: N/a
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, type 1 federal specification single treatment response Shelf Life: N/a
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, type 1 federal specification single treatment response Shelf Life: N/a Unit Of Measure:
Observation facility Special Features: 0.164-32 unc-2b threaded holes four places Material: Steel comp 630 Material Specification: Ams 5643 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35, type 1 federal specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: