NSN 5340-01-330-7650

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-330-7650

Mounting Hole Type:
Plain
First Leg Length:
0.910 inches
Second Leg Length:
1.380 inches
First Leg Hole Diameter:
Between 0.098 inches and 0.102 inches
Second Leg Hole Diameter:
Between 0.098 inches and 0.102 inches
Second Leg Distance From Edge To Hole Center Along Width:
Between 0.230 inches and 0.270 inches
Second Leg Distance From Edge To Hole Center Along Length:
Between 0.280 inches and 0.320 inches
First Leg Thickness:
Between 0.060 inches and 0.066 inches
Second Leg Thickness:
Between 0.060 inches and 0.066 inches
Center Section Height:
1.700 inches
Center Section Width:
Center Section Width:
2.300 inches
2.300 inches
2.300 inches Center Section Thickness:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius Second Leg Hole Arrangement Style:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius Second Leg Hole Arrangement Style: Two holes
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg:
2.300 inches Center Section Thickness: Between 0.060 inches and 0.066 inches First Leg Distance From Edge To Hole Center Along Width: Between 0.230 inches and 0.270 inches First Leg Distance From Edge To Hole Center Along Length: Between 0.280 inches and 0.320 inches First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style: Corner radius Second Leg Hole Arrangement Style: Two holes Second Leg Relationship To First Leg: Not identical

90.0 degrees

NSN 5340-01-330-7650

Double Angle Bracket - Page 2 of 2



Special Features:
Incl two clips
Material:
Nickel alloy 625
Material Specification:
Ams 5599 assn standard single material response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A042a0