
# NSN 5340-01-330-9887

Angle Bracket - Page 1 of 2





Mounting Hole Type:
Plain
First Leg Length:
0.700 inches
Second Leg Length:
0.700 inches
Second Leg Width:
1.895 inches
First Leg Hole Diameter:
Between 0.155 inches and 0.161 inches
Second Leg Hole Diameter:
Between 0.155 inches and 0.161 inches
Second Leg Distance Between Hole Centers Along Width:
1.420 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.237 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.202 inches
First Leg Thickness:
0.050 inches
Second Leg Thickness:
0.050 inches
First Leg Width:
2.250 inches
First Leg Distance Between Hole Centers Along Width:
1.750 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.200 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Cut out
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

# NSN 5340-01-330-9887

Angle Bracket - Page 2 of 2



## Second Leg Cutout Length:

0.500 inches

#### Second Leg Cutout Width:

1.095 inches

### **Special Features:**

Color forest green

#### Material:

Aluminum alloy 5052

## **Material Specification:**

Qq-a-250/8, h34 federal specification single material response

#### Surface Treatment:

Enamel

## Surface Treatment Specification:

Mil-e-5279 military specification single treatment response and mil-e-52835 military specification single treatment response

#### Style Designator:

Angle

# Shelf Life:

N/a

#### Unit Of Measure:

## Demilitarization:

No

---

Fiig:

A042a0

#### Mil-std (military Standard):

Mil-e-5279 spec.