

View Online at <https://aerobasegroup.com/nsn/5340-01-331-7698>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.000 inches and 1.120 inches

Second Leg Length:

Between 0.625 inches and 0.745 inches

Second Leg Width:

Between 0.685 inches and 0.775 inches

Second Leg End Width:

Between 0.365 inches and 0.385 inches

First Leg Hole Diameter:

Between 0.190 inches and 0.196 inches

Second Leg Hole Diameter:

Between 0.098 inches and 0.103 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.365 inches and 0.385 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.150 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.720 inches and 0.780 inches

First Leg End Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.350 inches and 0.410 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Second Leg Chamfer Angle:

Between 40.0 degrees and 50.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, t3 federal specification single material response

Surface Treatment:

Chromate zinc

Surface Treatment Specification:

Mil-p-8585 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-8585 spec.