

View Online at <https://aerobasegroup.com/nsn/5340-01-333-1260>

Mounting Hole Type:

Plain

First Leg Length:

0.850 inches

Second Leg Length:

1.500 inches

Second Leg Width:

2.700 inches

Second Leg Corner Radius:

Between 0.003 inches and 0.015 inches

First Leg Hole Diameter:

0.265 inches

Second Leg Hole Diameter:

0.052 inches

Second Leg Distance Between Hole Centers Along Width:

2.200 inches

Second Leg Distance Between Hole Centers Along Length:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

2.700 inches

First Leg Corner Radius:

Between 0.003 inches and 0.015 inches

First Leg Distance Between Hole Centers Along Width:

1.510 inches

First Leg Distance From Edge To Hole Center Along Width:

0.870 inches

First Leg Distance From Edge To Hole Center Along Length:

0.350 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

4 rivets and 2 nut plated included; hole in each nut plate 0.218 in. Diameter spaced 1.920 in. Btw ctrs

Material:

Steel comp 321 or steel comp 347

Material Specification:

Ams5510 assn standard 1st material response or ams5512 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

1516, code p military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0