

View Online at <https://aerobasegroup.com/nsn/5340-01-333-3572>

Mounting Hole Type:

Plain

First Leg Length:

1.120 inches

Second Leg Length:

1.880 inches

Reinforcement Method (non-core):

Turned edge both legs

Second Leg Width:

4.000 inches

First Leg Hole Diameter:

Between 0.342 inches and 0.349 inches

Second Leg Hole Diameter:

Between 0.248 inches and 0.255 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.000 inches

First Leg Distance Between Hole Centers Along Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.560 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Furn w/rod

Material:

Steel comp 1010 or steel comp 1020

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-83268 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-83268 spec.