

View Online at <https://aerobasegroup.com/nsn/5340-01-333-9986>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

3.500 inches

Reinforcement Method (non-core):

Turned edge second leg

Second Leg Width:

0.800 inches

Second Leg Corner Radius:

0.060 inches

First Leg Hole Diameter:

Between 0.169 inches and 0.175 inches

Second Leg Hole Diameter:

Between 0.127 inches and 0.133 inches

Second Leg Distance Between Hole Centers Along Width:

0.330 inches

Second Leg Distance Between Hole Centers Along Length:

1.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.290 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

0.800 inches

First Leg Corner Radius:

0.060 inches

First Leg Distance Between Hole Centers Along Width:

0.225 inches

First Leg Distance Between Hole Centers Along Length:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.350 inches

First Leg Distance From Edge To Hole Center Along Length:

0.240 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2 holes in turned edge

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t4 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.