

View Online at <https://aerobasegroup.com/nsn/5340-01-335-3505>

Special Features:

Bracket consists of aluminum plate, qq-a-250/11 alloy 6061-t6 or aluminum alloy, qq-a-250/8 alloy 5052-h34; 6.940 in. Min and 7.060 in. Maximum lg by 5.940 in. Min and 6.060 in. Maximum w; 4 mtg holes 0.295 in. Min and 0.304 in. Maximum dia, 0.181 in. Min and 0.195 in maximum thk; 2 supports, aluminum, qq-a-200/8 alloy t6511 or aluminum, qq-a-250/11, alloy 6061-t651; 1 support 1.220 in. Min and 1.280 in. Maximum lg by 0.600 in. Min and 0.650 in. Maximum square with 27 degrees min and 33 degrees slope cut on bottom; 1 support 4.180 in. Min and 4.240 in. Maximum lg by 0.600 in. Min and 0.650 in. Square with slope as above; gusset, aluminum alloy, qq-a-200/8 or qq-a-250/11, alloy 6061-t6; 2.850 in. Min and 2.910 in. Maximum lg by 1.470 in. Min and 1.530 in. Maximum h; sides on 27 degrees min and 33 degrees maximum angle; painted gloss white no. 17925, mil-p-23377

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0