

View Online at <https://aerobasegroup.com/nsn/5340-01-336-5416>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.380 inches

**Second Leg Length:**

1.550 inches

**Reinforcement Method (non-core):**

Gusset both legs

**Second Leg Width:**

1.300 inches

**First Leg Hole Diameter:**

0.128 inches

**Second Leg Hole Diameter:**

0.128 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.718 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.718 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.291 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.141 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

1.300 inches

**First Leg Distance Between Hole Centers Along Width:**

0.500 inches

**First Leg Distance Between Hole Centers Along Length:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.