## NSN 5340-01-337-1035

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-337-1035

Mounting Hole Type:
Plain
First Leg Length:
2.780 inches
Second Leg Length:
2.780 inches
Second Leg Width:
1.880 inches
Second Leg End Width:
1.380 inches
First Leg Hole Diameter:
Between 0.404 inches and 0.416 inches
Second Leg Hole Diameter:
Between 0.404 inches and 0.416 inches
Second Leg Distance Between Hole Centers Along Width:
1.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.440 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.437 inches
First Leg Thickness:
0.875 inches
Second Leg Thickness:
0.875 inches
Center Section Height:
5.000 inches
Center Section Width:
1.880 inches
Center Section Thickness:
0.380 inches
First Leg Width:
1.880 inches
First Leg End Width:
1.380 inches
First Leg Distance From Edge To Hole Center Along Width:
0.440 inches
First Leg Distance From Edge To Hole Center Along Length:
0.432 inches
First Leg Style:
Chamfered ends
First Leg Hole Arrangement Style:
One hole

## NSN 5340-01-337-1035

Double Angle Bracket - Page 2 of 2



Second Leg Style:
Chamfered ends
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
First Leg Chamfer Angle:
45.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-200/8 t6511 federal specification single material response
Surface Treatment:
Plastic polyurethane
Surface Treatment Specification:
Mil-c-46168 military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-46168 spec.