

View Online at <https://aerobasegroup.com/nsn/5340-01-340-0267>

Mounting Hole Type:

Plain

First Leg Length:

1.125 inches

Second Leg Length:

1.375 inches

Second Leg Width:

3.400 inches

Second Leg End Width:

2.310 inches

First Leg Hole Diameter:

Between 0.199 inches and 0.202 inches

Second Leg Hole Diameter:

0.390 inches

Second Leg Distance Between Hole Centers Along Width:

1.812 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.988 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.400 inches

First Leg End Width:

2.900 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.798 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.220 inches

First Leg Distance From Edge To Hole Center Along Width:

0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

0.545 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-200/11-t6511 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.