

View Online at <https://aerobasegroup.com/nsn/5340-01-340-0267>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.125 inches

**Second Leg Length:**

1.375 inches

**Second Leg Width:**

3.400 inches

**Second Leg End Width:**

2.310 inches

**First Leg Hole Diameter:**

Between 0.199 inches and 0.202 inches

**Second Leg Hole Diameter:**

0.390 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.812 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.988 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

3.400 inches

**First Leg End Width:**

2.900 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.798 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.220 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.340 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.545 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Material:**

Aluminum alloy 7075

**Material Specification:**

Qq-a-200/11-t6511 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.