

View Online at <https://aerobasegroup.com/nsn/5340-01-341-0826>

Slot Width:

Between 0.380 inches and 0.385 inches

Slot Length:

Between 0.507 inches and 0.513 inches

Offset Height:

Between 1.060 inches and 1.190 inches

Material And Location:

Steel, astm a108, grade 1010 handle pin err-100 err-100 or steel, astm a108, grade 1015 handle pin err-100 err-100 or steel, astm a108, grade 1016 handle pin err-100 err-100 or steel, astm a108, grade 1018 handle pin err-100 err-100 or steel, astm a108, grade 1020 handle pin err-100 err-100 or steel, astm a108, grade 1022 handle pin err-100 err-100 or steel, astm a108, grade 1025 handle pin err-100 err-100 steel, astm a575, grade 1010 handle err-100 err-100 or steel, astm a575, grade 1015 handle err-100 err-100 or steel, astm a575, grade 1020 handle err-100 err-100 or steel, astm a575, grade 1025 handle err-100 err-100

Surface Treatment And Location:

Zinc handle pin err-100 err-100 cadmium, qq-p-416, type 2, class 1 handle err-100 err-100 or cadmium, qq-p-416, type 2, class 3 handle err-100 err-100

Arm Style:

Offset

Cranklength:

7.380 inches

Handle Rotating Feature:

Included

Crank Throw Length:

6.310 inches

Mounting Facility:

Slot

Mounting Facility Slot Width:

Between 0.380 inches and 0.385 inches

Err Default:

Err default and err default

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25300